

Customer: SELDEN MID EUROPE
 Sales manager: Pieter Oenema
 Date created: 05-11-09
 Latest revision: 08-10-24
 Approved: 08-10-24 by PEW

Series production OK

General rig description

Conventional Fractional
 Deckstepped 1-spreader
 Untapered Sloop

Rig dimensions

Forestay height FH: 9.300 mm
 Main sail luff length P: 9.900 mm
 Boom height above deck BH: 800 mm
 Main sail foot length E: 3.850 mm
 Main boom sheet pos S: 3.750 mm
 Spinnaker pole length SPL: 3.355 mm

Chainplates dist. from cl mast

	Lateral	Long
Cap shrouds:	1409	641 mm (24,5°)
Aft lowers:	1385	629 mm
Deck above chainplates:	571 mm	
Deck above waterline:	1717 mm	

Hull and righting moment

Length: 8.980 mm
 Beam: 3.326 mm
 Draft: 1.680 mm
 Displacement: 3.670 Kg
 Ballast: 1.170 Kg
 Conventional keel, Equipped boat
 Heeling test RM: 21,0 kNm @30°

Spar sections

Mast: C175
 Boom: B135
 Spin. pole: S060

Furlex

Forestay: 106

Notes (6 lines)

Fractional gennaker halyard
 Permanent backstay optional.
 B&R rig
 RD1: 5mm R-screw 3/8" lower att. 750mm

Name changed from Etap 28 2008-10-24

